



Declaration of Compliance

Business Operator

Vikan A/S
Ræevevej 1
DK-7800 Skive
(+45) 96 14 26 00

Description

Item Number 29753

Plastic Material

Polypropylene, 98 %

Colour masterbatch

Blue, 2 %

Aluminium

Aluminium Alloy 5449 welded tubes

EU Compliance**AP(89)1**

All pigments in the masterbatch comply with resolution AP 89(1)

US FDA Compliance

All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) 21 CFR parts 170 to 199.

The polypropylene complies with FDA 21 CFR 177.1520 "olefin polymers".

The pigments in the masterbatch are listed under FDA 21 CFR 178.3297 „Colorants for Polymers“.

Non-food contact usage temperature

Minimum temperature: -20 °C
Maximum temperature: 80 °C

**General**

Equipment should be cleaned, disinfected and sterilised, as appropriate to its intended use, before use.

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Recommended sterilisation temperature (Autoclave): 121 °C

We will make the relevant background documentation available to the competent authorities, at their request.

Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

Date

3/20/2018

Made By

Stine Lønnerup Bislev
Hygiene and Compliance Manager